



Style Specifications — Contour Series

All floors shown or listed in this specification shall be Centiva Contour Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: ___ - ___ - C ___ - ___ in size ___" x ___"
Style Color Series Surface Edge

The Centiva Contour Series shall be constructed with a .032" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 04, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be D-2001 (wet-set), PS 5000 Plus (pressure sensitive), or EP 2000 (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

It is recommended that all Contour Stone and Festival tiles be installed tessellated or in one direction. Additional sizes, surface textures, and edge treatments are available upon request. Ask your Centiva consultant for more information.

CONTOUR PLANK

Classification:	ASTM F 1700-04 Class III Solid Vinyl Tile		
Construction:	Layered plank consisting of wearlayer, film, and backing		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	3" x 36", 4" x 36", 6" x 36", 7.2" x 48" plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost, Rough, Tick, Sawn		
Standard Colors:	26 designs/colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648-04	Critical Radiant Flux	Class I CRF > 0.45
	ASTM E 662-03	Smoke Density	< 450
	ASTM F 925-02	Chemical Reaction	Excellent
	Slip Resistance	ADA Compliant	Varies with surface texture
		FTC Slip Resistant Classified Product	