



# Style Specifications — Event Series

All floors shown or listed in this specification shall be Event Series by Centiva, Florence, AL, 35630.

Specific product shall be: \_\_\_ - \_\_\_ - \_\_\_ E \_\_\_ - \_\_\_ in size \_\_\_" x \_\_\_"  
Style Color Series Surface Edge

The Centiva Event Series shall be heterogeneous, resilient flooring with a .030" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose), or CENTI 2000 EP (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

*It is recommended that all Event square tiles be installed tessellated or in one direction.  
Additional sizes, surface textures, and edge treatments are available upon request.  
Ask your Centiva consultant for more information.*

## EVENT PLANK – OAK

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Layered product consisting of wearlayer, decorative film, and backing with pre- and post-consumer content		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	3" x 36", 4" x 36", or 6" x 36"		
<b>Edge:</b>	Square Edge (SE)		
<b>Surface Texture:</b>	Smoked Oak, Honey Oak, and Harvest Oak - Rustic (RU), Limed Oak - Natural Grain (NG), American Oak - Third Grain (TG)		
<b>Standard Colors:</b>	5 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ADA Compliant	Varies with surface texture
		FTC Slip Resistant	Classified Product