



Style Specifications — Victory Series

All floors shown or listed in this specification shall be Centiva Victory Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: ___ ___ V ___ ___ in size ___" x ___"
Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" high density wearlayer depending on product . All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 04, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be D-2001 (wet-set) or EP 2000 (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

GLITTER

Classification:	ASTM F 1700-04 Class III Solid Vinyl Tile		
Construction:	Multiple layers with glitter in wearlayer and pre-consumer recycled backing		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	9" x 9", 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost		
Standard Colors:	9 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648-04	Critical Radiant Flux	Class I CRF > 0.45
	ASTM E 662-03	Smoke Density	< 450
	ASTM F 925-02	Chemical Reaction	Excellent
	Slip Resistance	ADA Compliant	Varies with surface texture
		FTC Slip Resistant	Classified Product