



# Style Specifications — Victory Series

All floors shown or listed in this specification shall be Centiva Victory Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: \_\_\_ - \_\_\_ - \_\_\_ V \_\_\_ - \_\_\_ in size \_\_\_" x \_\_\_"  
Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" high density wearlayer depending on product . All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 04, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be D-2001 (wet-set) or EP 2000 (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

## MINERAL CHIP

<b>Classification:</b>	ASTM F 1700-04 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple color chips scattered throughout homogeneous tile		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	N/A, solid vinyl tile		
<b>Size:</b>	9" x 9", 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel, Deep Bevel		
<b>Surface Texture:</b>	Frost, Pathway, Slate		
<b>Standard Colors:</b>	6 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648-04	Critical Radiant Flux	Class I CRF > 0.45
	ASTM E 662-03	Smoke Density	< 450
	ASTM F 925-02	Chemical Reaction	Excellent
	Slip Resistance	ADA Compliant	Varies with surface texture
		FTC Slip Resistant	Classified Product