



Style Specifications – Victory Series

All floors shown or listed in this specification shall be Centiva Victory Series by International Floors of America, Inc., Florence, AL, 35630.

Specific product shall be: ___ ___ ___ V ___ ___ in size ___" x ___"
Style Color Series Surface Edge

The Centiva Victory Series shall be multi-layered with an overall gauge of .120" (3 mm) nominal. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at www.centiva.com.

STRIA

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing made from 100% pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	(SR) Stria		
Standard Colors:	8 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF > 0.45
	ASTM E 662	Smoke Density	< 450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product